



ALR 37/56 mm

GBK 50W S.C. Bay 12V 25D FR 1CT


Delivers high lumen output and excellent color rendering for precise accent and display lighting. Philips Halogen Aluminum Reflector Lamps provide continuous color and high luminous intensity for precise accent and display lighting. These lamps offer a rated average life ranging from 2000 hours and feature excellent beam qualities for accent or ambient lighting.

Product data

General Information		Mechanical and Housing	
Cap-Base	BA15S [BA15s]	Bulb Finish	Frosted
Philips Code	6439/FR	Cap-Base Information	-
Operating Position	UNIVERSAL [Any or Universal (U)]	Approval and Application	
ANSI Code Halogen	GBK	Energy Efficiency Label (EEL)	-
Light Technical		Luminaire Design Requirements	
Beam Angle (Nom)	25 °	Bulb Temperature (Max)	250 °C
Luminous Intensity (Max)	2000 cd	Cap-Base Temperature (Max)	350 °C
Correlated Color Temperature (Nom)	3000 K	Product Data	
Color Rendering Index (Nom)	100	Full product code	904667734091960
Operating and Electrical		Order product name	GBK 50W S.C. Bay 12V 25D FR 1CT
Power (Rated) (Nom)	50 W	EAN/UPC - Product	046677340919
Lamp Current (Nom)	4.17 A	Order code	924001617119
Starting Time (Nom)	0.0 s	Numerator - Quantity Per Pack	1
Voltage (Nom)	12 V	Numerator - Packs per outer box	50
Controls and Dimming		Material Nr. (12NC)	924001617119
Dimmable	Yes	Net Weight (Plece)	39.000 g
		ILCOS Code	HMGII/F-50-12-B15d-37/22

ALR 37/56 mm

Dimensional drawing



Alu 50W B15d 12V R56 25D FR

Product	D (max)	C (max)
GBK 50W S.C. Bay 12V 25D FR 1CT	58 mm	58 mm

